

List No. 9257

APPLEBY SERVICE ITEMS

1 Gang Architrave Flush Steel Installation Box 28mm Depth



- Robust & reliable
- Multiple knockout cable entry points

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	27 mm	
Width	27 mm	
Depth	28 mm	
Inner depth	28 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. 9258/GV
APPLEBY SERVICE ITEMS

2 Gang Architrave Flush Steel Installation Box 28mm Depth



- Robust & reliable
- Multiple knockout cable entry points
- External size: Length: 133mm; Width: 29mm; Depth: 27.5mm
- Internal size: Length: 130.6mm; Width: 26.6mm; Depth: 26.3mm

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	133 mm	
Width	29 mm	
Depth	27.5 mm	
Inner depth	26.3 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB615
APPLEBY SERVICE ITEMS

1 Gang Adjustable Lug Flush Steel Installation Box 35mm
Depth



- Robust & reliable
- Multiple knockout cable entry points
- 1 x 25mm Knockout
- 11 x 20mm Knockouts

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	68.3 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB618
APPLEBY SERVICE ITEMS

1 Gang Adjustable Lug Flush Steel Installation Box 47mm
Depth



- Robust & reliable
- Multiple knockout cable entry points

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	68.3 mm	
Depth	47 mm	
Inner depth	47 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB619
APPLEBY SERVICE ITEMS

1 Gang Dry Lining Installation Box with Adjustable Lugs 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data		Revision Date: 25/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	83 mm	
Width	83 mm	
Depth	36 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Plastic	
Halogen free	Yes	
Surface protection	Untreated	
Colour	White	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB623
APPLEBY SERVICE ITEMS

1 Gang Adjustable Lug Flush Steel Installation Box 16mm
Depth



- Robust & reliable
- Multiple knockout cable entry points

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	70 mm	
Width	70 mm	
Depth	16 mm	
Inner depth	16 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB625
APPLEBY SERVICE ITEMS

2 Gang Adjustable Lug Flush Steel Installation Box 35mm Depth



- Robust & reliable
- Multiple knockout cable entry points
- 4 x 25mm Knockouts
- 12 x 20mm Knockouts

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	129 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB628
APPLEBY SERVICE ITEMS

2 Gang Adjustable Lug Flush Steel Installation Box 47mm
Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	129 mm	
Depth	47 mm	
Inner depth	47 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB629
APPLEBY SERVICE ITEMS

2 Gang Dry Lining Installation Box with Adjustable Lugs 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data		Revision Date: 25/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	133 mm	
Width	83 mm	
Depth	36 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Plastic	
Halogen free	Yes	
Surface protection	Untreated	
Colour	White	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB631

APPLEBY SERVICE ITEMS

2 Gang Dry Lining Installation Box with Adjustable Lugs 47mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data		Revision Date: 25/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	133 mm	
Width	83 mm	
Depth	48 mm	
Inner depth	47 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Plastic	
Halogen free	Yes	
Surface protection	Untreated	
Colour	White	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB632
APPLEBY SERVICE ITEMS

1 Gang Dry Lining Installation Box with Adjustable Lugs 47mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data		Revision Date: 25/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	83 mm	
Width	83 mm	
Depth	48 mm	
Inner depth	47 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Plastic	
Halogen free	Yes	
Surface protection	Untreated	
Colour	White	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB633
APPLEBY SERVICE ITEMS

2 Gang Adjustable Lug Flush Steel Installation Box 16mm
Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	129 mm	
Depth	16 mm	
Inner depth	16 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB636

APPLEBY SERVICE ITEMS

Dual 1 Gang Flush Steel Installation Box 35mm Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Double	
Length	68.3 mm	
Width	154 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	2	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. .



List No. SB637

APPLEBY SERVICE ITEMS

Dual Accessory (Single Gang x 2) Dry Lining Installation Box
with Adjustable Lugs 35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data

Revision Date: 25/02/2025

CE Conformity	Yes
UKCA Conformity	Yes
Mounting method	Flush-mounted
Shape	Rectangular
Construction type	Device connection box (round/square)
Model	Double
Length	168 mm
Width	83 mm
Depth	36 mm
Inner depth	35 mm
For number of electric fittings	2
Mounting switching equipment	Screwing
With screws	No
Material	Plastic
Halogen free	Yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Cover model	Other
Cover attachment	Screwed

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB638

APPLEBY SERVICE ITEMS

Dual Accessory (Single Gang + Double Gang) Dry Lining
Installation Box with Adjustable Lugs 35mm

- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm



Product Specification Data		Revision Date: 25/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Double	
Length	218 mm	
Width	83 mm	
Depth	36 mm	
Inner depth	35 mm	
For number of electric fittings	2	
Mounting switching equipment	Screwing	
With screws	No	
Material	Plastic	
Halogen free	Yes	
Surface protection	Untreated	
Colour	White	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.

List No. SB639

APPLEBY SERVICE ITEMS

Circular Dry Lining Installation Box with 2 x 20mm Knockouts
35mm



- Made from flame retardant thermoplastic
- Tough yellow nylon lugs have large bearing faces for superior strength
- Large flange around the front matches profile of accessory front plates and prevents slipping into the cavity
- 25mm base knockout plus 2 side cable entry points.
- Appropriate for fitting board thicknesses from 6.35-15mm

Product Specification Data

Revision Date: 25/02/2025

CE Conformity	Yes
UKCA Conformity	Yes
Mounting method	Flush-mounted
Shape	Oval
Construction type	Device connection box (round/square)
Model	Single
Diameter	80 mm
Depth	36 mm
Inner depth	35 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	No
Material	Plastic
Halogen free	Yes
Surface protection	Untreated
Colour	White
Degree of protection (IP)	Other
Cover model	Other
Cover attachment	Screwed

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB641
APPLEBY SERVICE ITEMS
16mm MI Terminal Circular Box



- Robust & reliable
- Multiple knockout cable entry points

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Hollow ceiling	
Shape	Round	
Construction type	Device connection box (round/square)	
Model	Single	
Diameter	50.8 mm	
Depth	16 mm	
Inner depth	16 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. **SB642**
APPLEBY SERVICE ITEMS
16mm MI Through Circular Box

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Hollow ceiling	
Shape	Round	
Construction type	Device connection box (round/square)	
Model	Single	
Diameter	50.8 mm	
Depth	16 mm	
Inner depth	16 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB646

APPLEBY SERVICE ITEMS

3 Gang Fixed Lug Flush Steel Installation Box 35mm Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	189 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB655
APPLEBY SERVICE ITEMS

1 Gang Adjustable Lug Flush Steel Installation Box 25mm
Depth



- Robust & reliable
- Multiple knockout cable entry points

Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Device connection box (round/square)	
Model	Single	
Length	70 mm	
Width	70 mm	
Depth	25 mm	
Inner depth	25 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB665
APPLEBY SERVICE ITEMS

2 Gang Adjustable Lug Flush Steel Installation Box 25mm
Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	68.3 mm	
Width	129 mm	
Depth	25 mm	
Inner depth	25 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB676
APPLEBY SERVICE ITEMS

Dual 1 Gang Adjustable Lug Flush Steel Installation Box
25mm Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Double	
Length	68.3 mm	
Width	154 mm	
Depth	25 mm	
Inner depth	25 mm	
For number of electric fittings	2	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB677

SERVICE ITEMS

1 Gang Flush Steel Extension Box 16mm Depth



- Robust & reliable
- Extension accessory for increased installation depth

Product Specification Data

Revision Date: 27/03/2025

Product Standard/s	BS 4662
CE Conformity	No
WEEE Symbol	No
G Mark	No
Mounting method	Flush-mounted
Shape	Square
Construction type	Other
Model	Single
Length	70 mm
Width	70 mm
Depth	16 mm
Inner depth	16 mm
For number of electric fittings	1
Mounting switching equipment	Screwing
With screws	No
Material	Steel
Halogen free	Yes
Surface protection	Hot-dip galvanized
Colour	Grey
Degree of protection (IP)	Other
Cover model	Other
Cover attachment	Screwed

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



IMAGE
NOT AVAILABLE

For more information
please contact the
Technical Services
Department

- Robust & reliable
- Extension accessory for increased installation depth

Product Specification Data		Revision Date: 24/02/2025
Product Standard/s	BS 4662	
CE Conformity	No	
WEEE Symbol	No	
G Mark	No	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Other	
Model	Double	
Length	68.3 mm	
Width	129 mm	
Depth	16 mm	
Inner depth	16 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB679

SERVICE ITEMS

1 Gang Flush Steel Extension Box 25mm Depth



- Robust & reliable
- Extension accessory for increased installation depth

Product Specification Data		Revision Date: 24/02/2025
Product Standard/s	BS 4662	
CE Conformity	No	
WEEE Symbol	No	
G Mark	No	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Other	
Model	Single	
Length	68.3 mm	
Width	68.3 mm	
Depth	25 mm	
Inner depth	25 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB680

SERVICE ITEMS

2 Gang Flush Steel Extension Box 25mm Depth

- Robust & reliable
- Extension accessory for increased installation depth



Product Specification Data		Revision Date: 24/02/2025
Product Standard/s	BS 4662	
CE Conformity	No	
WEEE Symbol	No	
G Mark	No	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Other	
Model	Double	
Length	68.3 mm	
Width	129 mm	
Depth	25 mm	
Inner depth	25 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB681

SERVICE ITEMS

1 Gang Flush Steel Extension Box 35mm Depth



- Robust & reliable
- Extension accessory for increased installation depth

Product Specification Data		Revision Date: 24/02/2025
Product Standard/s	BS 4662	
CE Conformity	No	
WEEE Symbol	No	
G Mark	No	
Mounting method	Flush-mounted	
Shape	Square	
Construction type	Other	
Model	Single	
Length	68.3 mm	
Width	68.3 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB682

SERVICE ITEMS

2 Gang Flush Steel Extension Box 35mm Depth

- Robust & reliable
- Extension accessory for increased installation depth



Product Specification Data		Revision Date: 24/02/2025
Product Standard/s	BS 4662	
CE Conformity	No	
WEEE Symbol	No	
G Mark	No	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Other	
Model	Double	
Length	68.3 mm	
Width	129 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.



List No. SB695
APPLEBY SERVICE ITEMS

Flush Steel Installation Box for Volex Accessories Lounge
Plate 35mm Depth

- Robust & reliable
- Multiple knockout cable entry points



Product Specification Data		Revision Date: 24/02/2025
CE Conformity	Yes	
UKCA Conformity	Yes	
Mounting method	Flush-mounted	
Shape	Rectangular	
Construction type	Device connection box (round/square)	
Model	Single	
Length	194 mm	
Width	253 mm	
Depth	35 mm	
Inner depth	35 mm	
For number of electric fittings	1	
Mounting switching equipment	Screwing	
With screws	No	
Material	Steel	
Halogen free	Yes	
Surface protection	Hot-dip galvanized	
Colour	Grey	
Degree of protection (IP)	Other	
Cover model	Other	
Cover attachment	Screwed	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing.

